


DORNIER 3

Castello Officine s.r.l. | Fraz. Bulliana 30/D
 13835 VALDILANA | BIELLA | ITALY
 T. ++39 015 75144 | F. ++39 015 756826
 castello@temple-castello.com
 www.temple-castello.com



<p>DOR - 301 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Heavy, blanket, linen, wool, terry towellng High Shrinkage from 2.5 mm to 1.00 mm 22 DO3A22D000 - 30 DO3A30D000</p>	<p>22 DO3A22D000</p>  <p>260 mm</p>
<p>DOR - 302 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Medium, medium-heavy, wool, cotton, denim, corduroy, etc. High Shrinkage, temple cut from 1.5 mm to 0.50 mm 22 DO3B22D000 - 30 DO3B30D000</p>	<p>22 DO3B22D000</p>  <p>260 mm</p>
<p>DOR - 303 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Very heavy, terry, technical, etc. High Shrinkage from 2.5 mm to 1.5 mm 22 DO3C22D000 - 30 DO3C30D000</p>	<p>22 DO3C22D000</p>  <p>260 mm</p>
<p>DOR - 304 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Medium-light, fine, shirting, wool, cotton n16 n30, etc. Medium Shrinkage, temple cut from 1.00 mm to 0.75 mm 22 DO3G22D000 - 30 DO3G30D000</p>	<p>22 DO3G22D000</p>  <p>260 mm</p>
<p>DOR - 305 FABRIC</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Medium-light, fine, sheet, elastic fabrics, etc. Medium Shrinkage, temple cut from 1.00 mm to 0.55 mm 22 DO3L22D000 - 30 DO3L30D000</p>	<p>22 DO3L22D000</p>  <p>260 mm</p>
<p>DOR - 306 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Fine, shirting, cotton, etc. Medium-low Temple cut from 1.00 mm to 0.30 mm 22 DO3N22D000 - 30 DO3N30D000</p>	<p>22 DO3N22D000</p>  <p>260 mm</p>
<p>DOR - 307 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Fine, shirting, cotton, etc. Medium-low Temple cut from 1.00 mm to 0.30 mm 21 DO3L21DP14 - 29 DO3L29DP14</p>	<p>21 DO3L21DP14</p>  <p>260 mm</p>
<p>DOR - 308 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Fine, popline, shirting, etc. Low Temple cut from 0.75 mm to 0.30 mm 21 DO3N21DP14 - 29 DO3N29DP14</p>	<p>21 DO3N21DP14</p>  <p>260 mm</p>
<p>DOR - 309 FABRICS</p> <p>CONTRACTION PROBLEM PIN LENGHT RINGS N./CODE</p>	<p>Medium, medium-light, wool, cotton, silk, shirting Medium Selvedge keep from 1.00 mm to 0.50 mm 24 DO3F66252440 - 32 DO3F66253240</p>	<p>24 DO3F66252440</p>  <p>260 mm</p>



DORNIER 3

<p>DOR - 310 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Medium, medium-light, wool, cotton, silk, shirting</p> <p>Medium-low</p> <p>Selvedge keep</p> <p>from 1.00 mm to 0.50 mm</p> <p>6x105mm DO3Z662512 - 6x150mm DO3Z662522</p>	<p>6x105mm DO3Z662512</p> <p>260 mm</p>
<p>DOR - 311 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Light, shirting, cotton, silk</p> <p>Low</p> <p>Selvedge keep</p> <p>from 1.00 mm to 0.50 mm</p> <p>4x105 mm DO3Z462512 - 4x150 mm DO3Z462522</p>	<p>4x105 mm DO3Z462512</p> <p>260 mm</p>
<p>DOR - 312 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Medium, medium-heavy, denim, technical, corduroy</p> <p>Medium-high</p> <p>Shrinkage, temple cut, selvedge keep</p> <p>1.00 mm</p> <p>6 1904255</p>	<p>6 1904255</p> <p>260 mm</p>
<p>DOR - 313 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Light, cotton, silk, filament</p> <p>Low</p> <p>Temple cut</p> <p>from 1.00 mm to 0.50 mm</p> <p>4.20° DO3L462500 - 4.24° DO3L464500</p>	<p>4.20° DO3L462500</p> <p>218 mm</p>
<p>DOR - 314 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Medium-light, synthetic, silk, wool, etc.</p> <p>Medium-low</p> <p>Temple cut</p> <p>from 1.00 mm to 0.50 mm</p> <p>6.20° DO3L662500 - 6.24° DO3L664500</p>	<p>6.20° DO3L662500</p> <p>218 mm</p>
<p>DOR - 315 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Light, cotton, silk, filament</p> <p>Medium-low</p> <p>Selvedge keep</p> <p>1.00 mm</p> <p>2x105 mm DO3Z2N2512 - 2x150 mm DO3Z2N2522</p>	<p>2x105 mm DO3Z2N2512</p> <p>260 mm</p>
<p>DOR - 316 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Light, cotton, silk, filament</p> <p>Low</p> <p>Selvedge keep</p> <p>1.00 mm</p> <p>2 DO3C2N2500 - 3 DO3C3N2500</p>	<p>2 DO3C2N2500</p> <p>212 mm</p>
<p>DOR - 317 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>Fringe</p> <p>Medium</p> <p>Warp cut</p> <p>from 1.00 mm to 0.50 mm</p> <p>19 DO3G19F000</p>	<p>19 DO3G19F000</p> <p>260 mm</p>
<p>DOR - 318 FABRICS</p> <p>CONTRACTION PROBLEM</p> <p>PIN LENGHT RINGS N./CODE</p>	<p>AUXILIARY TEMPLE for leno-selvedge</p> <p>All</p> <p>Low, medium, high</p> <p>False selvedge</p> <p>1.50 mm, 1.00 mm, 1.00mm</p> <p>2 GE0U02S3203 - 4 GE0U04S3205 - 4 GE0U04S62205</p>	<p>2 GE0U02S3203 4 GE0U04S3205 4 GE0U04S62205</p>

